

NAME

zip_source_zip_file, **zip_source_zip_file_create** - create data source from zip file

LIBRARY

libzip (-lzip)

SYNOPSIS

```
#include <zip.h>
```

```
zip_source_t *
```

```
zip_source_zip_file(zip_t *archive, zip_t *srcarchive, zip_uint64_t srcidx, zip_flags_t flags,  
zip_uint64_t start, zip_int64_t length, const char *password);
```

```
zip_source_t *
```

```
zip_source_zip_file_create(zip_t *srcarchive, zip_uint64_t srcidx, zip_flags_t flags, zip_uint64_t start,  
zip_int64_t length, const char *password, zip_error_t *error);
```

DESCRIPTION

The functions **zip_source_zip_file()** and **zip_source_zip_file_create()** create a zip source from a file in a zip archive. The *srcarchive* argument is the (open) zip archive containing the source zip file at index *srcidx*. *length* bytes from offset *start* will be used in the zip_source. If *length* is -1, the rest of the file, starting from *start*, is used.

If you intend to copy a file from one archive to another, using the flag `ZIP_FL_COMPRESSED` is more efficient, as it avoids recompressing the file data.

Supported flags are:

ZIP_FL_COMPRESSED

Get the compressed data. This is only supported if the complete file data is requested (*start* == 0 and *length* == -1). This is not supported for changed data. Default is uncompressed.

ZIP_FL_ENCRYPTED Get the encrypted data. (This flag implies `ZIP_FL_COMPRESSED`.) This is only supported if the complete file data is requested (*start* == 0 and *length* == -1). Default is decrypted.

ZIP_FL_UNCHANGED Try to get the original data without any changes that may have been made to *srcarchive* after opening it.

RETURN VALUES

Upon successful completion, the created source is returned. Otherwise, NULL is returned and the error code in *archive* or *error* is set to indicate the error.

ERRORS

zip_source_zip_file() and **zip_source_zip_file_create()** fail if:

[ZIP_ER_CHANGED]

Unchanged data was requested, but it is not available.

[ZIP_ER_INVALID] *srcarchive*, *srcidx*, *start*, or *length* are invalid.

[ZIP_ER_MEMORY]

Required memory could not be allocated.

Additionally, it can return all error codes from **zip_stat_index()** and **zip_fopen_index()**.

SEE ALSO

libzip(3), zip_file_add(3), zip_file_replace(3), zip_source(3)

HISTORY

zip_source_zip_file() and **zip_source_zip_file_create()** were added in libzip 1.10.0.

AUTHORS

Dieter Baron <dillo@nih.at> and Thomas Klausner <tk@giga.or.at>